



AVerMedia® AverVision Visualiser Main Unit: 3-Years Carry-In Limited Warranty

Model	Spec	Weight	SRP	Remarks
CP150	3.2M Pixels, Lens:f1=9.6mm Output Resolution: XGA (1024x768) Zoom:16X Total Zoom (2X Optical + 8X Digital Zoom) Frame Rate 24fps(Max), Manual Focus Storage: Built-in Memory (Max:80 Image) Flicker Filter Control 2 Levels, Image & Video Recording (USB to PC) negative/positive conversion: yes Night View: Yes	2.4 kg	2,600	
CP300	3.2M Pixels, Image Sensor: 1/2" CMOS Output Resolution: WXGA (1280x720) Zoom:16X Total Zoom (2X Optical + 8X Digital Zoom) Frame Rate 24fps(Max), Manual Focus Storage: Built-in Memory (Max:80 Image) Flicker Filter Control 2 Levels, Laser positioning Guide Image & Video Recording (USB to PC) negative/positive conversion: yes Night View: Yes	2.4 kg	3,250	

Laser Pointer / Wireless Presenter

Brand	Model	Description	SRP	Remarks
I-Pointer		laser pointer, Page up/down	180	
X-Pointer	XP140	Long Battery Life	228	Premium Series, c/w Pouch
X-Pointer	XP200TR	Remote Mouse & Keyboard	350	Premium Series, c/w Pouch
X-Pointer	XPG110	Green Laser	280	Visibility: 200meter++

Laser Pointer / Wireless Presenter

Brand	Model	Description	SRP	Remarks
I-Pointer	IP100	Laser Pointer, Page up/down	180	
X-Pointer	XP140	Long Battery Life	228	Premium Series, c/w Pouch
X-Pointer	XP200TR	Remote Mouse & Keyboard	350	Premium Series, c/w Pouch
X-Pointer	XPG110	Green Laser Pointer	280	Visibility: 200meter++
X-Pointer	XPG200	Green Laser Pointer with Wireless Presenter	549	Visibility: 200meter++

VGA Splitter / Switcher

Brand	Model	Description	SRP	Remarks
Aten	VS82	1 Video In (Male), 2 Video Out (Female), 250MHz, Signal Range: up to 65meter	100	
Aten	VS84	1 Video In (Male), 4 Video Out (Female), 250MHz, Signal Range: up to 65meter	130	
Aten	VS88	1 Video In (Male), 8 Video Out (Female), 200MHz, Signal Range: up to 65meter	220	
Aten	VS94A	1 Video In (Male), 4 Video Out (Female), 350MHz, Signal Range: up to 65meter	260	
Aten	VS0204	2 Video(male)/Audio(Green) In, 4 Video(female)/Audio(Green) Out,	690	Each of the 4 video outs can toggle between

Motorised Projector Lift

Type	Model	Description	SRP	Remarks
Scissors Lift	SC-20	Dimension 760W x 600D x 500Hmm, Max. Lowering 2.0M	5,250	suitable for Hall
Scissors Lift	SC-40	Dimension 760W x 600D x 550Hmm, Max. Lowering 4.0M	5,500	suitable for Hall
Scissors Lift	SC-60	Dimension 760W x 600D x 650Hmm, Max. Lowering 6.0M	5,750	suitable for Hall
Cube Lift	XLT-CB 330	Dimension : 540W x 540D x 320H, Max Lowering 300mm	2,800	suitable for Meeting Room
Cube Lift	XLT-CB 380	Dimension : 540W x 540D x 370H, Max Lowering 350mm	2,900	suitable for Meeting Room
Cube Lift	XLT-CB 550	Dimension : 540W x 540D x 520H, Max Lowering 500mm	3,200	suitable for Meeting Room

Projector Screen & Ceiling Bracket

Brand	Model	Description	SRP	Remarks
	6ft x 6ft	Wall Mount	180	
	8ft x 8ft	Wall Mount	550	
	6ft x 6ft	Tripod	220	
	8ft x 8ft	Tripod	580	
	6ft x 6ft	Motorised with Remote Control	900	
	8ft x 8ft	Motorised with Remote Control	1,300	
	12ft x 12ft	Motorised with Remote Control	2,800	
	16ft W x 12ft H	Motorised with Remote Control (5 Yr Wty on Motor)	18,500	
	24ft W x 18ft H	Motorised with Remote Control (5 Yr Wty on Motor)	32,000	
	Bracket	Universal Ceiling Bracket (up to 1meter)	280	with Cable Management